

DG - 400 adjustable

Pressure Control Blower
made of
Aluminium

For inflating foil cushion roofs



The blowers can be supplied in any RAL colour

Standard RAL colour 7035


Nolting - pressure control blower made of aluminium for permanent operation

- max. air output up to 1,000 m³/h
- efficient fan motor (conformity to ERP)
- variable-speed fan motor
- pressure setting at pressure switch
- pressure metering in one cushion
- pressure reading at unit
- low noise operation
- carrier handle
- low weight



Additional control

- Min. pressure alarm
- Max. pressure alarm
- optical and audible signal
- battery with maintenance charging
- on / off switch for alarm system



GUSTAV NOLTING GmbH

Orbker Straße 38 | D-32758 Detmold
Phone +49 (0) 52 31 . 60 01-0
Fax +49 (0) 52 31 . 60 01-51
info@gustav-nolting-gmbh.de
www.gustav-nolting-gmbh.de



Connection -
pressure
measuring
hose

Technical Data		
Type	DG-	400
Air output	m ³ /h	up to 1,000
Intake air	mm	ND 50
External pressure	Pa	up to 600
Electrical connection	V/Hz	230 / 50
Motor capacity	W	170
Length	mm	400
Width	mm	400
Height	mm	465
Weight	kilos	20
Fresh air		with filter
Blow-out		without non-return valve

